



REV MARK	ECN NO.	日期 DATE	修改 DRAW	核准 APPROVE

**FEATURES:**

**1 Electrical Test:**

A. Safety Voltage/Current Rating 150V ac, at 1.5A.  
 B. Dielectric with standing 1000V/DC/min, <0.5A.  
 C. Insulation Resistance:>500M Ω, 1000V./min  
 D. Contact Resistance:<20M Ω

**2 Mechanical:**

A. Cable-to-Plug tensile strength-20LBs(89N)min.  
 B. Durability:750 mating cycles.  
 3 Operation Temperature:-40℃~+85℃.  
 4. Environmental compliance  
 A. the products are compliant with the RoHS, and REACH ETC.  
 5. Safety standards:UL E239590

**特征:**

**1 电气特性:**

A. 额定电压150伏特AC, 额定电流1.5A  
 B. 耐电压测试: 小于0.5安培1000伏特DC/一分钟。  
 C. 绝缘抗隆: 1000伏特DC/一分钟, 大于500百萬歐姆  
 D. 接觸陰坑: 不大于20m Ω (毫歐姆)

**2 機械特性:**

A. 拉力測試-電纜至插座張力強度至少一分鐘20磅 (89N)  
 B. 耐力測試-拔插測試750次以上。  
 3 使用溫度範圍: -40℃~+85℃  
 4 環保符合性:  
 A. 產品符合RoHS, REACH等環保規格。  
 5 安全標準: UL E239590

注: 帶▲为重点尺寸控制

BLADE:	A5	B4	B7	B9	B20	A3	B7	<input type="checkbox"/> 屏蔽壳 Shell	<input type="checkbox"/> 黄铜 Brass	<input type="checkbox"/> 铁 Steel	1
Drawing								Au: <input type="checkbox"/> G/F" <input type="checkbox"/> 1u" <input type="checkbox"/> 3u" <input type="checkbox"/> Ni <input type="checkbox"/> 80u"			
Mark								胶壳 PC(聚碳酸酯) <input type="checkbox"/> 94-V0 <input checked="" type="checkbox"/> 94-V2			
BLADE:	A4	A10	B6	B10	金片 (PIN针) Contacts		<input checked="" type="checkbox"/> 黄铜 Brass	<input type="checkbox"/> 磷铜 Phosphor copper	8		
Drawing					<input type="checkbox"/> G/F" <input type="checkbox"/> 1u" <input type="checkbox"/> 3u" <input type="checkbox"/> 6u"	<input type="checkbox"/> 15u" <input type="checkbox"/> 30u" <input type="checkbox"/> 50u" <input type="checkbox"/> OTHER					
Mark											

TELEMAX <sup>®</sup> SHENZHEN TELEMAX TECHNOLOGY CO.,LTD						
品名规格 DESCRIPTION				页次 SHEET		1/1
产品编号 PRODUCT NO			单位 UNIT	比例 SCALE	1:1	版本 EDITI
DIMENSION IN mm(Inch) TOLERANCE UNLESS OTHERWISE SPECIFIED			第三视角法 THIRD ANGLE PROJECTION		制图 DRAWN	日期 DATE
x, x ±0.2					审核 CHECK	日期 DATE
x, xx ±0.10					批准 APPRO	日期 DATE
x, xxx ±0.050					日期 DATE	2018. 10. 07