

TYPE:

1. RJ45 CAT6A SHIELDED TOOLLESS PLUG
2. COLOUR: WHITE

CABLE MATCHED:

1. SOILD AND STRANDED
2. 22AWG/23AWG/24AWG

ELECTRICAL:


1. CONTACT RESISTANCE: 20m OHM
2. INSULATION RESISTANCE: $\leq 500M$ OHM @100 V DC
3. WITHSTAND VOLTAGE: DC1000V AC700V RMS 60HZ, I MIN
4. CAT6A PERMANENT LINK: CONFORM TO ANSI/TIA/EIA 568B. 2-10

ENVIRONMENTAL:

1. STORAGE: -40° / $+70^{\circ}$
2. OPERATION: -10° / $+60^{\circ}$

MECHANICAL:

1. PLASTIC MATERIAL: NEW PC
2. SHIELDED MATERIAL: ZINC ALLOY NICKEL PLATING
3. TERMINAL PINS: PHOSPHOR BRONZE, ZIN PLATING
4. RJ45 CONTACT LIFE: 750 TIMES MIN
5. IDC TERMINAL LIFE: 250 TIMES MIN

TOLERANCE		SHENZHEN TELEX TECHNOLOGY Co., LTD				
X.X	± 0.2	SCALE	NONE		REV	A
X.XX	± 0.1					
X.XXX	± 0.05	UNIT	mm	SHEET	1/1	DWG NO.
ANGLE	$\pm 2^{\circ}$					
DRAWN BY	Chen	DATE	2020.4.27			
CHECK BY						
APPD BY		PART NO. TM04C6ATLC				