


RJ45 Cat.5E/6/6A/7/7A/8 FTP Toolless Plug



Type:

- RJ45 Cat.5E/6/6A/7/7A/8 FTP toolless plug
- Color: Silver

Physicals

- Plastic Parts: PC
- Pin: Phosphor bronze gold over nickel plating, golden plated 3u"
- PCB: FR-4 UL94V-0
- IDC housing: Zine alloy plating nickel
- IDC CONDUCTOR: Phosphor Bronze C5191 over nickel plating, tin-plating

Electrical:

- Insulation Resistance: 500M OHM 100V/DC/1Min
- Contact Resistance: ≤ 20 M OHM
- Current Rating: 1.5 Amps
- DC Resistance: 0.1 OHM
- DC/AC Volt Endurance: 1000V/AC 750V 1min

Mechanical:

- Plug Insertion Life ≥ 750 Cycles
- Durability: ≥ 20 Termination Cycles
- Plug Insertion Force: ≤ 20 N
- Plug Retention Force: ≥ 20 N
- Retentiveness Of Insertion Structure: 50N 60 ± 5 s
- Accommodates 22AWG~24AWG Solid and stranded

Environmental:

- Operating Temperature: -20°C to 75°C
- storage Temperature: -40°C to 75°C
- Operating Humidity: 10%-90%RH
- mates With Modular Plug Conforming to FCC Part 68, Subpart F
- Standards: ISO/IEC 11801, ANSI/TIA568.2-D, YD/T 926.3-2009

For More Information:

Email: sales@telemax.cn

www.telemax.cn

www.telemaxcable.com